



Gree Waterproof Leakage Repair Tape

Product Description

Gree Super strong Waterproofing Leakage Repair Tape Ideal to seal cracks and holes. Stops leak instantly, coated with super strong rubber adhesive. Also works underwater.

Product Structure



- Coated with natural rubber adhesive
- PET Film

Product Features & Application

- Smooth surface pipe, hose, plastic, PVC, glass, tile, iron.
- Can patch, bond, seal and repair.
- Repair water pipes or leaky containers.
- Applied to hot or cold, wet or dry condition.

Product Properties

Description	Test result	Unit
Total thickness	0.7mm±0.02mm	Mic
Tensile strength	≥24	MPa
Elongation	≥35%	%
Weight resistant	280-300	N
Peel adhesion to steel	≥40 N	N/in
Water absorption	<0.5 %	%
Water Leakage 20° Cx9h	No leakage	No leakage
Proper Temperature	-20 ~ +60	°C

Application Technique

Clean the surface well with dry cloth.

Ensure surface is free from grease, oil, stains and dust.

Apply pressure after applying the tape to get better bonding.

Avoid touching the tapes exposed adhesive surface in order to keep full adhesive performance.

Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 HRS at 23°C.

All technical information and data mentioned above are only test values from RATCs laboratory, they shall not be considered as specification standards or guarantee values. The user is responsible for determining whether Gree product is fit for specific purposes or applications by conducting suitability testing, before placing a purchase order.

